

Poly-Tek Continuous Fence



The Poly-Tek Continuous Fence system offers buyers an affordable and attractive alternative to expensive traditional masonry block wall fencing.

Comprising of a high density EPS core and sandwiched between 2 x 4.5mm Pre Rendered FC (Fibre Cement) sheets the Poly-Tek Continuous Fence provides great acoustic properties (perfect for busy or main roads), superior strength and modern aesthetics.



Installation time frames and huge cost savings are the stand out advantages of the Poly-Tek Continuous Fence system as required labour is minimised. There is no need for bricklayers, renderers or expensive and time consuming strip footings. Installation is a breeze whether it be carried out by one of our trade professionals or for the D.I.Y consumer. Once installed, all that is required is painting and any outdoor acrylic paint is suitable for this.



Due to the 'in house' coating process continuity of the render finish is achieved and the surface membrane of the finish will ensure you won't experience the unsightly cracks that almost certainly appear with a block wall fence.

The Poly-Tek Continuous Fence is supplied as a standard height of 1800mm (made up of 3 x 600mm panels) however for residential projects whereby you wish to incorporate an insert style of some description a 600mm, 900mm or 1200mm high fence may be more suitable. On roadside style projects multiple panels of 1200mm in height would prove more appropriate. Different height configurations can be achieved by mixing the panel heights.



The fence thickness is 100mm and each standard panel is supplied at 2.4m long and is cut back on site if necessary. Cut outs for mailboxes or electrical boxes can also be easily accommodated when on site.